

**Listing of Claims:**

1. (Currently amended) A catheter assembly comprising:  
a hollow sheath having a proximal portion, ~~and a tip, and a hub at the~~  
proximal portion;  
an elongate operative element slidably and rotatably housed within the  
sheath, the operative element comprising a distal end and a proximal end;  
the elongate operative element comprising a relatively stiff initial section  
extending from the proximal end thereof, wherein the stiff initial section extends distally beyond  
the hub to permit the elongate operative element to move back and forth within the hollow  
sheath;  
a rotatable combined connector secured to the proximal end of the  
operative element so as to be proximal to the hub, said combined connector comprising a  
data/information connector and a mechanical connector; and said combined connector  
comprising an angled rotary alignment surface that is adapted to blind mate with a corresponding  
connector of a drive unit that has an angled rotary alignment surface.
2. (Original) The catheter assembly according to claim 1 wherein said  
data/information connector comprises an electrical connector.
3. (Original) The catheter assembly according to claim 1 wherein said  
mechanical connector comprises a rotary drive connector.
4. (Previously presented) The catheter assembly according to claim 3  
wherein said rotary drive connector comprises a drive surface which simultaneously extends  
axially and circumferentially.
5. (Original) The catheter assembly according to claim 1 wherein said  
combined connector comprises a rotary alignment surface.

6. (Previously presented) The catheter assembly according to claim 1 wherein said elongate operative element comprises an imaging cable having an image element at said distal end thereof.

7. (Original) The catheter assembly according to claim 1 wherein said initial section comprises a metal tube.

8. (Original) The catheter assembly according to claim 1 further comprising a fluid seal between said proximal portion of said sheath and the initial section of the elongate operative element.

9. (Previously presented) The catheter system according to claim 1 wherein said elongate operative element comprises a flexible imaging core and a relatively stiff tube at the proximal end thereof to create a relatively stiff initial section of the elongate operative element extending from the proximal end thereof.

10-32 (Canceled)

33. (Withdrawn)

34. (New) A catheter assembly comprising:  
a hollow sheath having a proximal portion and a tip;  
an elongate operative element slidably and rotatably housed within the sheath, the operative element comprising a distal end and a proximal end;  
the elongate operative element comprising a relatively stiff initial section extending from the proximal end thereof, wherein the stiff initial section is stiffer than an adjacent distal portion of the elongate operative element;  
a rotatable combined connector secured to the proximal end of the operative element, said combined connector comprising a data/information connector and a mechanical connector; and said combined connector comprising an angled rotary alignment

Appl. No. 09/970,314

Amdt. dated February 27, 2004

Reply to Office Action of December 15, 200

PATENT

surface that is adapted to blind mate with a corresponding connector of a drive unit that has an angled rotary alignment surface.